

## EUROLITE LED PST-12W 3000K Spot

Narrow beam pinspot with 12 W warm white (WW) LED

Art. No.: 51916110

GTIN: 4026397735956



**List price: 47.48 €**

incl. 19% VAT.

### Features:

- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- 1 powerful LED 12 W COB (chip-on-board) warm white (WW)
- Focus manual
- Spot effect
- Gobo wheel with static gobos, 4 reduction gobos
- The device is cooled by passive convection cooling
- Control via plug and play
- Very high color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; installation; restaurants, bars and hotels; video and photography
- Silent operation
- Application possibility: Suspended; on stand; wall mounting

#### Package contents

- 1 x spotlight, 1 x key, 1 x user manual

### Logistic

EAN / GTIN: 4026397735956

Weight: 0,50 kg

Length: 0.19 m

Width: 0.18 m

Height: 0.08 m

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug built-in

Lamp type:	LED lamp
LED type:	1 x 12 W COB (chip-on-board) warm white (WW)
Equipment:	Focus manual
Gobos:	Gobo wheel with static gobos, 4 reduction gobos
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	12° monochrome 11° monochrome 10° monochrome 7° monochrome
Beam angle (1/10 peak):	16° 14° 12° 9°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	1m: 3308 lx, 3m: 441 lx, 6m: 119 lx
Luminous flux:	1200 lm rated light flux at 90°
Housing color:	Black matte
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 19 cm Width: 8,5 cm Height: 13,5 cm Diameter: Ø 6 cm
Weight:	0,44 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	E
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm