

EUROLITE LED PST-10 QCL spot

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916152 GTIN: 4026397690132











List price: 106.98 € incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free
- Strobe effect
- With a beam angle of 4°
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

1 x device, 1 x remote control, 1 x diffusor cover, 1 x lamp clamping ring, 1 x battery, 1 x user

Logistic

EAN / GTIN: 4026397690132

Weight: 1,20 kg Length: 0.15 m Width: 0.15 m Heigth: 0.29 m

Technical specifications:

Power supply:		
Protection class: Protection class Protection class Protection class: Protection class Protection class: Protection class Protecti	Power supply:	100-240 V AC, 50/60 Hz
Protection class: Protection class II Power connection: Fixed power supply cord with Euro plug Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Fuse replaceable Lamp type: LED lamp LED: 1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Fost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Hight: 20,3 cm <	Power consumption:	12 W
Power connection: Fixed power supply cord with Euro plug Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Fuse replaceable Lamp type: LED lamp LED: 1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4* Beam angle (1/12 peak): Spot 4* Frost filter 16* Beam angle (1/10 peak): Spot 7* Frost filter 36* Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Diameter Ø 7,7 cm	IP classification:	IP20
Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Fuse replaceable Lamp type: LED lamp LED: 1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Eeam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Spot 7° Frost filter 36° Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm	Protection class:	Protection class II
Fuse:	Power connection:	Fixed power supply cord with Euro plug
LED lamp LED: 1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Plastic, 1 mm </td <td>Cable length:</td> <td>Approx. 1 m</td>	Cable length:	Approx. 1 m
LED: 1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Plastic, 1 mm Color: <td>Fuse:</td> <td>5 x 20 mm, T 0,5 A Fuse replaceable</td>	Fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
(homogenous color mix) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø7,7 cm	Lamp type:	LED lamp
Flash rate: DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø7,7 cm	LED:	
DMX channels: Cooling: Passive convection cooling Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Display type: 4 digit 7-segment LED display Material: Dimensions: Length: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Material: Diffusor cover Material: Diffusor cover Material: Plastic, 1 mm Diffusor cover Material: Plastic, 1 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Diameter: Ø 7,7 cm	Color temperature:	6500K
Cooling: Passive convection cooling Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø7,7 cm	Flash rate:	0 - 20 Hz
Control: IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	DMX channels:	3; 4; 5; 6; 9
light via Microphone; Master/slave function Preprogrammed in: Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Cooling:	Passive convection cooling
EASY SHOW 3	Control:	
Beam angle: Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Preprogrammed in:	
Beam angle (1/2 peak): Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Projection:	Flicker-free
Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Beam angle:	4°
Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Diameter: Ø 7,7 cm	Beam angle (1/2 peak):	•
Attachment system: Double bracket Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Beam angle (1/10 peak):	
Display type: 4 digit 7-segment LED display Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Housing color:	Black
Material: Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Attachment system:	Double bracket
Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Display type:	4 digit 7-segment LED display
Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Material:	Plastic
Weight: 1,03 kg Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	Dimensions:	Width: 16,3 cm
Noise classification: Class 0 (no noise at all) Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm		
Photobiological safety: Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm		
Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm		
Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	·	
Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	-	1 x Ø11mm
Diffusor cover Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm	<u> </u>	
Material: Plastic, 1 mm Color: Frost Dimensions: Diameter: Ø 7,7 cm		****
Color: Frost Dimensions: Diameter: Ø 7,7 cm		Plastic, 1 mm
Dimensions: Diameter: Ø 7,7 cm		

Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting