

EUROLITE LED PST-10 QCL Spot

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916152

GTIN: 4026397690132



List price: 106.98 €

incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
 - 1 powerful LED 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - 9 integrated show programs
 - Direct color selection for 19 preset colors
 - The device is cooled by passive convection cooling
 - Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
 - Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Colorchief
 - Flicker-free
 - With a beam angle of 4°
 - With double bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x remote control, 1 x battery, 1 x frost filter, 1 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397690132

Weight: 1,20 kg

Length: 0.15 m

Width: 0.15 m

Height: 0.29 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H05VVH2-F
Cable length:	Approx. 1 m
Fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0,5 - 24 Hz
DMX channels:	3; 4; 5; 6; 9
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	23400 Hz
Beam angle:	4°
Beam angle (1/2 peak):	Spot 4° Frost filter 16°
Beam angle (1/10 peak):	Spot 7° Frost filter 36°
Color temperature:	6500K
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm
Weight:	1,03 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Frost filter	

Material:	Plastic, 1 mm
Dimensions:	Diameter: Ø 7,7 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting