Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

eurolite

EUROLITE LED IP PST-10W 2700K Pinspot

Weather-proof pinspot (IP65) with strong 10 W LED in warm white (WW)

Art. No.: 51916159

GTIN: 4026397617993



Features:

- Compact aluminum housing
- 1 powerful LED 10 W high-power warm white (WW) _
- Beam effect
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 4°
- With mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended -Package contents
- 1 x device, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm² H05RN-F

Logistic

EAN / GTIN: 4026397617993 Weight: 0,76 kg Length: 0.11 m Width: 0.13 m Heigth: 0.17 m





Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	1 x 10 W high-power warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	4°
Beam angle (1/2 peak):	4°
Beam angle (1/10 peak):	6°
Color temperature:	2700K
Illuminance in Lux (lx):	1m: 30222 lx, 3m: 4331 lx, 6m: 1130 lx
Luminous flux:	803 lm
Housing color:	Grey
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 10,5 cm
	Depth: 15 cm
	Height: 14,7 cm
Weight:	0,70 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1066944
Mounting bracket	
Diameter mounting holes:	3 x Ø6mm
Material:	Aluminum, 2 mm
	-