

## EUROLITE LED Z-PAR 18x8W QCL Zoom

Bright LED spotlight with motorized zoom and RGBW color mixing

Art. No.: 51916505

GTIN: 4026397752120



### Description:

Despite its compact design, this fixture offers an impressively wide zoom range from 12° to 72°, along with strong light output.

Color generation is handled by 18 LEDs with RGBW color mixing, allowing for a wide range of colors and white tones.

### Features:

- 18 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Zoom motor driven
- Dimmer electronic; colors adjustable; color change adjustable; color fade adjustable; color blend stepless
- Wash effect; strobe effect
- Integrated show programs
- Direct color selection for 8 preset colors
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- With a beam angle of 12° - 72°
- Flicker-free
- Mains input and output for power linking up to 8 units
- The device is cooled by temperature-controlled fan
- 4 digit 7-segment LED display
- With double bracket
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended; on stand
- Fixtures available for Light Captain

### Logistic

EAN / GTIN: 4026397752120

Weight: 4,04 kg

Length: 0.29 m

Width: 0.29 m

Height: 0.30 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	18 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.6 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	7; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	22000 Hz
Beam angle:	12° - 72°
Beam angle (1/2 peak):	12 - 49°
Beam angle (1/10 peak):	30 - 72°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Diameter mounting holes:	1 x Ø12mm
Material:	Aluminum casting
Dimensions:	Width: 28.22 cm Depth: 15.85 cm Height: 29.5 cm
Weight:	3.62 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

1 x spotlight  
1 x user manual  
1 x power cord  
1 x XLR cable