

## EUROLITE LED D-4000 Beam Effect

Extremely bright derby with 3 W LED in 8 colors, incl. IR remote control

Art. No.: 51917318

GTIN: 4026397699753



**List price: 201.11 €**

incl. 19% VAT.

### Features:

- Precision lenses fill the room with countless rotating beams
  - 8 powerful LEDs 3 W SMD 3535 R/G/B/W/A/C/Y/P
  - Color change adjustable; color fade adjustable; Dimmer electronic; Rotation speed stepless
  - Multi beam effect; Strobe effect
  - 4 integrated show programs
  - Direct color selection for 25 preset colors
  - The device is cooled by low-noise cooling fan
  - Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - With a beam angle of 100°
  - With Mounting bracket
  - 4 digit 7-segment LED display
  - Preprogrammed in Light Captain; EASY SHOW 2
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; small rental
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397699753

Weight: 3,05 kg

Length: 0.34 m

Width: 0.32 m

Height: 0.21 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	35 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
LED:	8 x 3 W SMD 3535 R/G/B/W/A/C/Y/P
Flash rate:	0 - 20 Hz
DMX channels:	5; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2
Beam angle:	100°
Beam angle (1/2 peak):	100°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 28,9 cm Depth: 28,7 cm Height: 19,9 cm
Weight:	2,60 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting