

EUROLITE LED D-4000 Beam Effect

Extremely bright derby with 3 W LED in 8 colors, incl. IR remote control

Art. No.: 51917318

GTIN: 4026397699753



Features:

- Precision lenses fill the room with countless rotating beams
- 8 LEDs 3 W SMD 3535 R/G/B/W/A/C/Y/P
- Color change adjustable; color fade adjustable; Dimmer electronic; Rotation speed stepless
- Multi beam effect; strobe effect
- 4 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; EASY SHOW 2
- Flicker-free
- With a beam angle of 100°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397699753

Weight: 3,05 kg

Length: 0.34 m

Width: 0.32 m

Height: 0.21 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 35 W

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 3 W SMD 3535 R/G/B/W/A/C/Y/P
Flash rate:	0.4 - 18 Hz
DMX channels:	5; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle (1/2 peak):	100°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 28.9 cm Depth: 28.7 cm Height: 19.9 cm
Weight:	2.60 kg
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x user manual