

## EUROLITE LED DMF-4 Hybrid Flower Effect

Spotlight with flower- and stroboscope effect, incl. IR remote control

Art. No.: 51918563

GTIN: 4026397695052



**List price: 95.08 €**

incl. 19% VAT.

### Features:

- 2 strips with white LEDs provide fast, dynamic strobe effects
  - 70 powerful LEDs 5 mm R/G/B
  - 12 powerful LEDs SMD 5050 cold white (CW)
  - Flower effect; Strobe effect
  - 4 integrated show programs
  - Direct color selection for 8 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Preprogrammed in Light Captain
  - With a beam angle of 37°
  - With Mounting bracket
  - 4 digit 7-segment LED display
  - For application areas such as: Clubs/dancing school; Party room; small rental
  - Very quiet working noise
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x device, 1 x power cord, 1 x user manual, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397695052

Weight: 1,45 kg

Length: 0.23 m

Width: 0.22 m

Height: 0.13 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 10 W

IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	T 0,5 A Fuse replaceable
LED:	70 x 5 mm R/G/B 12 x SMD 5050 cold white (CW)
DMX channels:	7
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Beam angle:	37°
Beam angle (1/2 peak):	37°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 19,4 cm Width: 20,2 cm Height: 12,3 cm
Weight:	1,30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting