

## EUROLITE LED SCY-500 QCL Beam Effect

LED effect light with RGBW-LEDs, dynamic color effects and stroboscope

Art. No.: 51918674

GTIN: 4026397692273



**List price: 415.31 €**

incl. 19% VAT.

### Features:

- 5 powerful LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) <BR> LEDs controlled separately
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Fan effect; Strobe effect
  - 3 integrated show programs
  - Direct color selection for 15 preset colors
  - The device is cooled by low-noise cooling fan
  - Control via stand-alone; DMX; IR remote control; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - With a beam angle of 4°
  - With Mounting bracket
  - 4 digit 7-segment LED display
  - Preprogrammed in Light Captain
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
  - Very quiet working noise
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x light effect, 1 x user manual, 1 x remote control, 1 x battery, 1 x power cord

### Logistic

EAN / GTIN: 4026397692273  
Weight: 3,90 kg  
Length: 0.45 m  
Width: 0.29 m  
Height: 0.16 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
LED:	5 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 6; 9; 20; 23
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Beam angle:	4°
Beam angle (1/2 peak):	4° Multi beam effect 90°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 39 cm Depth: 25 cm Height: 18 cm
Weight:	3,33 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting