

EUROLITE LED B-100 Hypno Single Ball Beam Effect

LED beam effect with RGBW color mixing and 8 RGB hypno rings

Art. No.: 51918825

GTIN: 4026397726992



List price: 296.31 €

incl. 19% VAT.

Features:

- Fuzzy sound control: program continues automatically during periods without music or bass-beat
 - 8 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW
 - 96 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB
 - Dimmer electronic; color fade; color change; color blend; Rotation speed; Rotation direction
 - Multi beam effect
 - 2 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; master/slave function
 - Preprogrammed in Light Captain; Colorchief
 - Flicker-free
 - With omega bracket; with mounting bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Standing; suspended
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord, 2 x omega bracket, 2 x screw

Logistic

EAN / GTIN: 4026397726992

Weight: 5,10 kg

Length: 0.32 m

Width: 0.25 m

Height: 0.42 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 10 W SMD 5050 4in1 QCL RGBW 96 x 0,2 W SMD 5050 3in1 TCL RGB
Max. TILT movement:	360° positioning infinity
Max. PAN movement:	540°
Flash rate:	0 - 20 Hz
DMX channels:	16
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; master/slave function
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Illuminance in Lux (lx):	Red (R) 1m: 4812 lx, 3m: 1146 lx, 6m: 271 lx Green (G) 1m: 8250 lx, 3m: 2434 lx, 6m: 723 lx Blue (B) 1m: 3015 lx, 3m: 604 lx, 6m: 153 lx Cold white (CW) 1m: 14513 lx, 3m: 3918 lx, 6m: 817 lx
Housing color:	Black
Attachment system:	Omega bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Diameter mounting holes:	4 x Ø5mm
Material:	Plastic
Dimensions:	Width: 27,0 cm Depth: 21,0 cm Height: 35,5 cm
Weight:	4,50 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting