

EUROLITE LED PR-100/32 Pixel DMX rail

DMX controlled pixel tube with RGB color mixing

Art. No.: 51928609

GTIN: 4026397684551



List price: 232.05 €

incl. 19% VAT.

Features:

- DMX and power terminals intelligently designed for easy wiring
 - Front cover: milky
 - 96 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
32 segments controlled separately
 - Color blend stepless; color change adjustable; colors preset; Dimmer electronic
 - 12 integrated show programs
 - Direct color selection for 17 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; sound to light via microphone
 - Preprogrammed in Light Captain
 - With a beam angle of 120°
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Suspended; wall mounting
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397684551

Weight: 2,60 kg

Length: 1.04 m

Width: 0.10 m

Height: 0.20 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|------------------------|-------------------------------------------------------------------------------------------------|
| Power consumption: | 30 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 96 x SMD 5050 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0,25 - 10 Hz |
| DMX channels: | 3; 5; 8; 48; 96 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone |
| Preprogrammed in: | Light Captain |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 99,9 cm Width: 5,95 cm Height: 13,2 cm |
| Weight: | 2,10 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |