

## EUROLITE LED PIX-12 Swing QCL Zoom Bar

Art. No.: 51930386

Motorized tilttable LED light effect bar with 12 high-performance LEDs, two zoom ranges from 2° to 28° and 164 effect LEDs



**List price: 1486.31 €**

incl. 19% VAT.

### Features:

- 12 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix)<BR> LEDs controlled separately
- 164 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Positioning within 180° TILT
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; background color adjustable; program speed adjustable; running light adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable; pulse-width modulation variable
- Beam effect; strobe effect; uplight effect
- 6 integrated show programs
- The device is cooled by cooling fan at the base
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; blackout; auto)
- With a beam angle of 2° - 28°
- With a beam angle of 120°
- With omega bracket
- Monochrome LCD display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; concerts/FoH's; rental
- Application possibility: Standing; suspended

### Package contents

### Logistic

EAN / GTIN: 4026397737127

Weight: 17,50 kg

Length: 1.07 m

Width: 0.37 m

Height: 0.19 m

- 1 x light effect, 1 x user manual, 1 x power cord, 2 x omega bracket

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	310 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1,5 mm <sup>2</sup> H05VV-F
Cable length:	1,4 m
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 40 W 4in1 QCL RGBW (homogenous color mix) 164 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	180° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	28; 34; 67
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version
Cooling:	1 x cooling fan at the base
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM
Preprogrammed in:	Light Captain
Projection:	Flicker-free
DMX fail mode:	Hold; blackout; auto
Beam angle:	120° 2° - 28°
Beam angle (1/2 peak):	Ambient light 120° multicolor
Beam angle (1/2 peak):	Beam 2 - 20°
Beam angle (1/10 peak):	Beam 2 - 28°
Illuminance in Lux (lx):	Narrow red (R) 1m: 8706 lx, 3m: 1789 lx, 6m: 903 lx Narrow green (G) 1m: 12942 lx, 3m: 2762 lx, 6m: 1509 lx Narrow blue (B) 1m: 1924 lx, 3m: 470 lx, 6m: 257 lx Narrow cold white (CW) 1m: 13809 lx, 3m: 2917 lx, 6m: 1573 lx Narrow all 1m: 35732 lx, 3m: 7693 lx, 6m: 4097 lx

Wide red (R) 1m: 1884 lx, 3m: 513 lx, 6m: 148 lx  
Wide green (G) 1m: 3154 lx, 3m: 880 lx, 6m: 256 lx  
Wide blue (B) 1m: 538 lx, 3m: 152 lx, 6m: 44 lx  
Wide cold white (CW) 1m: 3275 lx, 3m: 885 lx, 6m: 257 lx  
Wide all 1m: 8576 lx, 3m: 2363 lx, 6m: 682 lx

Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Monochrome LCD display
USB port:	Type A
Transport aid:	4 x rubber feet
Material:	Metal, painted
Dimensions:	Width: 100 cm Depth: 12 cm Height: 28,5 cm
Weight:	15,70 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting