

## EUROLITE LED BAR-12 QCL RGB+WW Bar

LED light effect bar (1 m) with RGB+WW color mixing

Art. No.: 51930388

GTIN: 4026397716146



**List price: 184.45 €**

incl. 19% VAT.

### Features:

- 12 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
- 3 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Flicker-free
- Strobe effect
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Variable color temperature 2700 K - 8000 K
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Preprogrammed in EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended

### Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 2 x mounting bracket, 2 x washer, 2 x knurled screw

### Logistic

EAN / GTIN: 4026397716146

Weight: 3,12 kg

Length: 1.03 m

Width: 0.11 m

Height: 0.14 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	12 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Color temperature:	2700K - 8000K adjustable
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light J; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	2x Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 1,06 m Depth: 8,85 cm Height: 10,90 cm
Weight:	2,68 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting