

EUROLITE LED BAR-12 QCL RGB+WW Bar

LED light effect bar (1 m) with RGB+WW color mixing

Art. No.: 51930388

GTIN: 4026397716146



List price: 184.45 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 20°
- Variable color temperature 2700 K - 8000 K
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended
- **knurled screw**
- M6 thread
- **Package contents**
- 1 x bar, 1 x user manual, 1 x power cord, 2 x mounting bracket, 2 x washer, 2 x knurled screw

Logistic

EAN / GTIN: 4026397716146

Weight: 3,12 kg

Length: 1.03 m

Width: 0.11 m

Height: 0.14 m

Technical specifications:

| | |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 25 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Fuse: | T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 12 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 6; 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Beam angle (1/10 peak): | 33° |
| Color temperature: | 2700K - 8000K adjustable |
| Housing color: | Black |
| Attachment system: | 2x mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 106,00 cm Depth: 8,85 cm Height: 10,90 cm |
| Weight: | 2,68 kg |
| Noise classification: | Class 0 (no noise at all) |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Cable length: | Approx. 1,2 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm |
| Material: | Metal, 2 mm |
| Washer | |

| | |
|--------------------------|----------------------------------------------|
| Diameter mounting holes: | 1 x Ø9mm |
| Material: | Plastic, 3 mm |
| Color: | Black |
| Dimensions: | Diameter: Ø 2 cm |
| Knurled screw | |
| Thread: | M6 thread x 18 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |