

## EUROLITE LED BAR-12 QCL RGB+WW Bar

LED light effect bar (1 m) with RGB+WW color mixing

Art. No.: 51930388

GTIN: 4026397716146



### Features:

- 12 LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - 3 integrated show programs
  - Direct color selection for 20 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Fixtures available for EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
  - Flicker-free
  - With a beam angle of 20°
  - Variable color temperature 2700 K - 8000 K
  - With mounting bracket
  - 4 digit 7-segment LED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
  - Silent operation
  - Application possibility: Suspended
- knurled screw**
- M6 thread

### Logistic

EAN / GTIN: 4026397716146

Weight: 3,12 kg

Length: 1.03 m

Width: 0.11 m

Height: 0.14 m

## Technical specifications:

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                    |
| Power consumption:       | 25 W                                                                                                                                                                                      |
| IP classification:       | IP20                                                                                                                                                                                      |
| Protection class:        | Protection class I                                                                                                                                                                        |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                          |
| Power output:            | 1 x IEC connector (F) mounting version                                                                                                                                                    |
| Fuse:                    | T 1 A fuse replaceable                                                                                                                                                                    |
| Lamp type:               | LED lamp                                                                                                                                                                                  |
| LED type:                | 12 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)                                                                                                                                |
| Flash rate:              | 0 - 20 Hz                                                                                                                                                                                 |
| DMX channels:            | 2; 4; 5; 6; 9                                                                                                                                                                             |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                            |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                            |
| Cooling:                 | Passive convection cooling                                                                                                                                                                |
| Control:                 | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | EASY SHOW 1; Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                                                |
| Projection:              | Flicker-free                                                                                                                                                                              |
| Beam angle:              | 20°                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 20°                                                                                                                                                                                       |
| Beam angle (1/10 peak):  | 33°                                                                                                                                                                                       |
| Color temperature:       | 2700K - 8000K adjustable                                                                                                                                                                  |
| Housing color:           | Black                                                                                                                                                                                     |
| Attachment system:       | 2x mounting bracket                                                                                                                                                                       |
| Display type:            | 4 digit 7-segment LED display                                                                                                                                                             |
| Dimensions:              | Length: 106.00 cm<br>Depth: 8.85 cm<br>Height: 10.90 cm                                                                                                                                   |
| Weight:                  | 2.68 kg                                                                                                                                                                                   |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                                                                 |
| Cable construction:      | 3 x 0.75 mm² H05VV-F                                                                                                                                                                      |
| Cable length:            | Approx. 1.2 m                                                                                                                                                                             |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm                                                                                                                                                  |
| Material:                | Metal, 2 mm                                                                                                                                                                               |
| Color:                   | Black, matte                                                                                                                                                                              |
| Diameter mounting holes: | 1 x Ø9mm                                                                                                                                                                                  |
| Material:                | Plastic, 3 mm                                                                                                                                                                             |

|                  |                                              |
|------------------|----------------------------------------------|
| Color:           | Black                                        |
| Dimensions:      | Diameter: Ø 2 cm                             |
| Thread:          | M6 thread x 18 mm                            |
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

**Scope of delivery:**

---

- 1 x bar
- 1 x user manual
- 1 x power cord
- 2 x mounting bracket
- 2 x washer
- 2 x knurled screw