

**EUROLITE LED BAR-12 QCL RGBW Bar**  
LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBW LED

**Art. No.: 51930398**  
GTIN: 4026397603378



**Features:**

- 12 LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

**Logistic**

EAN / GTIN: 4026397603378  
Weight: 3,30 kg  
Length: 1.06 m  
Width: 0.14 m  
Heigth: 0.12 m

**Technical specifications:**

|                    |                        |
|--------------------|------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz |
| Power consumption: | 24 W                   |
| IP classification: | IP20                   |

|                          |                                                                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                   |
| Power output:            | 1 x IEC connector (F) mounting version                                                                                                             |
| Fuse:                    | 5 x 20 mm, T 0.5 A fuse replaceable                                                                                                                |
| Lamp type:               | LED lamp                                                                                                                                           |
| LED type:                | 12 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)                                                                                           |
| Flash rate:              | 0.5 - 24 Hz                                                                                                                                        |
| DMX channels:            | 2; 4; 5; 6; 9                                                                                                                                      |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                     |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                     |
| Cooling:                 | Passive convection cooling                                                                                                                         |
| Control:                 | Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Fixtures available for:  | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief        |
| Projection:              | Flicker-free                                                                                                                                       |
| Beam angle:              | 17°                                                                                                                                                |
| Beam angle (1/2 peak):   | 17°                                                                                                                                                |
| Beam angle (1/10 peak):  | 33°                                                                                                                                                |
| Housing color:           | Black                                                                                                                                              |
| Attachment system:       | Mounting bracket                                                                                                                                   |
| Display type:            | 4 digit 7-segment LED display                                                                                                                      |
| Dimensions:              | Length: 110 cm<br>Depth: 6.5 cm<br>Height: 10 cm                                                                                                   |
| Weight:                  | 2.85 kg                                                                                                                                            |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                          |
| Photobiological safety:  | Risk Group 0                                                                                                                                       |
| Cable construction:      | 3 x 0.75 mm² H05RN-F                                                                                                                               |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm                                                                                                           |
| Material:                | Metal                                                                                                                                              |
| Special product:         | Not designed for household room illumination                                                                                                       |
| Intended use:            | Show effect lighting                                                                                                                               |

## Scope of delivery:

1 x light effect  
 1 x power cord  
 2 x mounting bracket  
 2 x knurled screw  
 2 x washer  
 1 x user manual