

## EUROLITE LED PIX-7 Hybrid SCL Bar

Light effect bar with RGBA/CW/WW+UV LEDs and pixel control

Art. No.: 51930407

GTIN: 4026397643664



### Features:

- Each 7in1 LED can be controlled individually
- Mains input and output for power linking up to 8 units
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; Light Captain; Light´J
- Flicker-free
- With a beam angle of 18°
- With mounting bracket
- Silent operation
- light effect**
- 6 LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- strobes**
- 72 LEDs 0.5 W SMD 5050 3in1 TCL RGB (homogenous color mix)

### Logistic

EAN / GTIN: 4026397643664

Weight: 4,45 kg

Length: 0.54 m

Width: 0.16 m

Heigh: 0.23 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 50 W

IP classification: IP20

|                         |  |
|-------------------------|--|
| Power connection:       | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)   |
| Power output:           | 1 x P-Con (gray), mounting version   |
| Lamp type:              | LED lamp   |
| Flash rate:             | 0 - 20 Hz  |
| DMX channels:           | 3; 7; 9; 22; 43  |
| DMX input:              | 1 x 3-pin XLR (M) mounting version   |
| DMX output:             | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                | Passive convection cooling   |
| Control:                | Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | LED PC-Control 512; Light Captain; Light J   |
| Projection:             | Flicker-free   |
| Beam angle:             | 18°  |
| Beam angle (1/2 peak):  | 18°  |
| Beam angle (1/10 peak): | 35°  |
| Housing color:          | Black  |
| Attachment system:      | Mounting bracket   |
| Dimensions:             | Length: 50 cm<br>Depth: 10 cm<br>Height: 14.9 cm   |
| Weight:                 | 3.95 kg  |
| Noise classification:   | Class 0 (no noise at all)  |
| Photobiological safety: | Risk Group 0   |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in  |
| LED type:               | 72 x 0.5 W SMD 5050 3in1 TCL RGB (homogenous color mix)  |
| LED type:               | 6 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)  |
| Special product:        | Not designed for household room illumination   |
| Intended use:           | Show effect lighting   |

### Scope of delivery:

1 x remote control