

## EUROLITE LED PIX-12 QCL Bar

LED light bar with 12 x 4 W RGBW LED, pixel control and IR remote control

Art. No.: 51930426

GTIN: 4026397659115



**The article is no longer in our assortment.**

### Description:

LED bar with 12 x W RGBW LED, pixel control and IR remote control

The EUROLITE LED PIX-12 QCL bar features 12 powerful 4 W LEDs (4in1) in red, green, blue and white with a beam angle of 18°. It is suitable for professional applications, for example on show or theater stages.

The LED light bar is based on a stepless RGBW color mixing. The functions available are color change, color fade, dimmer and strobe effects. It is worth mentioning that you can control each LED individually and select 18 colors directly. Furthermore, there are five integrated show programs in auto and music mode. Addressing and settings can be made via the control unit with 4-digit LED display.

You can control the LED PIX-12 QCL either with the included infrared remote control, via DMX, QuickDMX via USB (optional) or by music control via the built-in microphone, whose sensitivity can be adjusted on the control board.

The P-Con power connectors allow you to connect up to eight devices in a row.

### Features:

- 12 powerful LEDs high-power 4in1 QCL RGBW (homogenous color mix)<BR> LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan

### Logistic

EAN / GTIN: 4026397659115

Weight: 6,45 kg

Length: 1.05 m

Width: 0.20 m

Height: 0.16 m

- Control via stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - With a beam angle of 18°
  - With Mounting bracket
  - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
  - Mains input and output for power linking up to 8 units
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Lamp type:	LED lamp
LED:	12 x high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 15; 52; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	36°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 1 m Depth: 16,5 cm Height: 11,1 cm
Weight:	5,55 kg
Photobiological safety:	Risk Group 0
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting