

# **EUROLITE LED PIX-144 RGB Bar**

Bar (100 cm) with 144 wide beam SMD LEDs (RGB), 8 segments

Art. No.: 51930439 GTIN: 4026397618037



**List price: 106.98 €** 

incl. 19% VAT.

#### Features:

- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)<BR>8 segments controlled separately
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain; Colorchief
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; mobile djs / entertainer
- Silent operation
- Application possibility: Suspended; wall mounting

### knurled screw

- M8 thread

#### Package contents

 1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

## **Technical specifications:**

Power supply:

100-240 V AC, 50/60 Hz

### Logistic

EAN / GTIN: 4026397618037

Weight: 1,86 kg Length: 1.05 m Width: 0.12 m Heigth: 0.11 m

Protection class   Protection	Power consumption:	25 W
Power connection:  Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)  Power output:  1 x IEC connector (F) mounting version  Fuse:  5 x 20 mm, T 1 A fuse replaceable  Lamp type:  LED lamp  LED type:  144 x SMD 5050 3in1 TCL RGB (homogenous color mix)  Fliash rate:  0,8 - 24 Hz  DMX channels:  3; 5; 6; 12; 24; 48  DMX input:  3-pin XLR (M) mounting version  DMX output:  3-pin XLR (M) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone  Preprogrammed in:  Light'J; LED PC-Control 512; Light Captain; Colorchief  Projection:  Flicker-free  PWM frequency:  13300 Hz  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  M8 thread x 16 mm  Diameter: Ø 2 cm  Legal specifications  Power cord  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	IP classification:	IP20
version power supply cord with safety plug (provided)  Power output: 1 x IEC connector (F) mounting version  Fuse: 5 x 20 mm, T 1 A fuse replaceable  LED lamp  LED type: 144 x SMD 5050 3in1 TCL RGB (homogenous color mix)  Flash rate: 0,8 - 24 Hz  DMX channels: 3, 5; 6; 12; 24; 48  DMX input: 3-pin XLR (M) mounting version  DMX output: 3-pin XLR (M) mounting version  Cooling: Passive convection cooling  Control: DMX; sound to light via microphone  Preprogrammed in: Light 3; LED PC-Control 512; Light Captain; Colorchief  Projection: Flicker-free  PWM frequency: 13300 Hz  Housing color: Black  Attachment system: 2x mounting bracket  Display type: 4 digit 7-segment LED display  Material: Aluminum casting  Dimensions: Length: 102 cm	Protection class:	Protection class I
Fuse:         5 x 20 mm, T 1 A fuse replaceable           Lamp type:         LED lamp           LED type:         144 x SMD 5050 3in1 TCL RGB (homogenous color mix)           Flash rate:         0,8 - 24 Hz           DMX channels:         3; 5; 6; 12; 24; 48           DMX input:         3-pin XLR (M) mounting version           DMX output:         3-pin XLR (F) mounting version           Cooling:         Passive convection cooling           Control:         DMX; sound to light via microphone           Preprogrammed in:         Light 7; LED PC-Control 512; Light Captain; Colorchief           Projection:         Flicker-free           PWM frequency:         13300 Hz           Housing color:         Black           Attachment system:         2x mounting bracket           Display type:         4 digit 7-segment LED display           Material:         Aluminum casting           Dimensions:         Length: 102 cm           Depth: 6,5 cm         Height: 8 cm           Weight:         1,54 kg           Noise classification:         Class 0 (no noise at all)           Power cord         Class 0 (no noise at all)           Cable construction:         3 x 0,75 mm² H05VV-F           Cable length:         Approx. 1,2 m	Power connection:	version power supply cord with safety plug
LED lamp  LED type:	Power output:	1 x IEC connector (F) mounting version
LED type: 144 x SMD 5050 3in1 TCL RGB (homogenous color mix)  Flash rate: 0,8 - 24 Hz  DMX channels: 3; 5; 6; 12; 24; 48  DMX input: 3-pin XLR (M) mounting version  DMX output: 3-pin XLR (F) mounting version  Cooling: Passive convection cooling  Control: DMX; sound to light via microphone  Preprogrammed in: Light 3; LED PC-Control 512; Light Captain; Colorchief  Projection: Flicker-free  PWM frequency: 13300 Hz  Housing color: Black  Attachment system: 2x mounting bracket  Display type: 4 digit 7-segment LED display  Material: Aluminum casting  Dimensions: Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight: 1,54 kg  Noise classification: Class 0 (no noise at all)  Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Fuse:	5 x 20 mm, T 1 A fuse replaceable
Color mix	Lamp type:	LED lamp
DMX channels:  3; 5; 6; 12; 24; 48  DMX input:  3-pin XLR (M) mounting version  DMX output:  3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone  Preprogrammed in:  Light J; LED PC-Control 512; Light Captain; Colorchief  Projection:  Flicker-free  PWM frequency:  13300 Hz  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	LED type:	,
DMX input:  3-pin XLR (M) mounting version  DMX output:  3-pin XLR (F) mounting version  Cooling:  Passive convection cooling  Control:  DMX; sound to light via microphone  Preprogrammed in:  Light'J; LED PC-Control 512; Light Captain; Colorchief  Projection:  Flicker-free  PWM frequency:  13300 Hz  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm  Depth: 6,5 cm  Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Flash rate:	0,8 - 24 Hz
DMX output:  3-pin XLR (F) mounting version  Cooling: Passive convection cooling  Control: DMX; sound to light via microphone  Preprogrammed in: Light 'J; LED PC-Control 512; Light Captain; Colorchief  Projection: Flicker-free  PWM frequency: 13300 Hz  Housing color: Black  Attachment system: 2x mounting bracket  Display type: 4 digit 7-segment LED display  Material: Aluminum casting  Dimensions: Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight: 1,54 kg  Noise classification: Class 0 (no noise at all)  Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	DMX channels:	3; 5; 6; 12; 24; 48
Cooling: Passive convection cooling Control: DMX; sound to light via microphone Preprogrammed in: Light'J; LED PC-Control 512; Light Captain; Colorchief Projection: Flicker-free PWM frequency: 13300 Hz Housing color: Black Attachment system: 2x mounting bracket Display type: 4 digit 7-segment LED display Material: Aluminum casting Dimensions: Length: 102 cm Depth: 6,5 cm Height: 8 cm Weight: 1,54 kg Noise classification: Class 0 (no noise at all) Power cord Cable construction: 3 x 0,75 mm² H05VV-F Cable length: Approx. 1,2 m Mounting bracket Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm Material: Metal, 2 mm Knurled screw Thread: M8 thread x 16 mm Washer Material: Rubber Dimensions: Dimensions: Height: 0,3 cm Diameter: Ø 2 cm Legal specifications Special product: Not designed for household room illumination	DMX input:	3-pin XLR (M) mounting version
Control:  DMX; sound to light via microphone  Preprogrammed in:  Light'J; LED PC-Control 512; Light Captain; Colorchief  Projection:  Flicker-free  PWM frequency:  13300 Hz  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version
Preprogrammed in:  Light'J; LED PC-Control 512; Light Captain; Colorchief  Projection:  Flicker-free  PWM frequency:  13300 Hz  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Cooling:	Passive convection cooling
Colorchief  Projection: Flicker-free  PWM frequency: 13300 Hz  Housing color: Black  Attachment system: 2x mounting bracket  Display type: 4 digit 7-segment LED display  Material: Aluminum casting  Dimensions: Length: 102 cm	Control:	DMX; sound to light via microphone
PWM frequency:  Housing color:  Black  Attachment system:  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Preprogrammed in:	
Housing color:  Attachment system:  2x mounting bracket  2x mounting bracket  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Projection:	Flicker-free
Attachment system:  Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	PWM frequency:	13300 Hz
Display type:  4 digit 7-segment LED display  Material:  Aluminum casting  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Housing color:	Black
Material:  Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Attachment system:	2x mounting bracket
Dimensions:  Length: 102 cm Depth: 6,5 cm Height: 8 cm  Weight:  1,54 kg  Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Depth: 6,5 cm Height: 8 cm  Weight: 1,54 kg  Noise classification: Class 0 (no noise at all)  Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Material:	Aluminum casting
Noise classification:  Class 0 (no noise at all)  Power cord  Cable construction:  3 x 0,75 mm² H05VV-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Dimensions:	Depth: 6,5 cm
Power cord  Cable construction: 3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Weight:	1,54 kg
Cable construction:  3 x 0,75 mm² H05VV-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
Cable length:  Mounting bracket  Diameter mounting holes:  1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Power cord	
Mounting bracket  Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Cable construction:	3 x 0,75 mm² H05VV-F
Diameter mounting holes: 1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm  Material: Metal, 2 mm  Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Cable length:	Approx. 1,2 m
Material:  Metal, 2 mm  Knurled screw  Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Mounting bracket	
Knurled screw  Thread: M8 thread x 16 mm  Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Diameter mounting holes:	1 x Ø11mm; 2 x Ø8mm; 1 x Ø8,5mm
Thread:  M8 thread x 16 mm  Washer  Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Material:	Metal, 2 mm
Washer  Material: Rubber  Dimensions: Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Knurled screw	
Material:  Rubber  Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Thread:	M8 thread x 16 mm
Dimensions:  Height: 0,3 cm Diameter: Ø 2 cm  Legal specifications  Special product:  Not designed for household room illumination	Washer	
Diameter: Ø 2 cm  Legal specifications  Special product: Not designed for household room illumination	Material:	Rubber
Special product: Not designed for household room illumination	Dimensions:	
Special product: Not designed for household room illumination	Legal specifications	
		Not designed for household room illumination