

EUROLITE LED BAR-252 RGBA 10mm 20° white

Versatile LED-RGBA color changer

Art. No.: 51930443 GTIN: 4026397429008



The article is no longer in our assortment.

Features:

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies max.19 channels)
- 4, 6 or 19 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Functions: Static colors, RGBA color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 252 x 10 mm LED
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- Available in 2 LED beam angles: 20° or 40°
- Available in black or white housing
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free with brilliant light radiation
- Control via DMX
- Preprogrammed in Light'J

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|--------------------|-----------------|
| Power consumption: | 24,00 W |
| IP classification: | IP20 |

Logistic

EAN / GTIN: 4026397429008

Weight: 3,00 kg Length: 1.09 m Width: 0.14 m Heigth: 0.14 m

| Control: | DMX |
|-------------------------|--|
| Preprogrammed in: | Light'J |
| Dimensions: | Length: 1,08 m |
| | Depth: 6,5 cm |
| | Height: 9 cm |
| Weight: | 2,65 kg |
| DMX channels: | max. 19: 4 / 6 / 19 |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| LED type: | 10 mm |
| LED number: | 252 |
| Beam angle: | 20° |
| Dimensions (L x W x H): | 1075 x 65 x 90 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |