



List price: 1486.31 €

incl. 19% VAT.

Features:

- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended
- <p>EUROLITE LED Space Tube 100 for HST Hoist
- <p class="featureSatz">Modern LED ambient light with DMX control
- Vertical and horizontal position with two hoists possible
- Particularly impressive when used in larger quantities
- 60 powerful LEDs high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; Dimmer electronic; effect speed adjustable
- The device is cooled by passive convection cooling
- Control via DMX
- For application areas such as: Wedding/gala/events; Clubs/dancing school; restaurants, bars and hotels

Package contents

- 1 x light effect
- <p>EUROLITE HST-200 Hoist
- <p class="featureSatz">Hoist for LED Space Balls 20, 35 and LED Space Tube 100
- Control via DMX
- Preprogrammed in LED PC-Control 512
- With Omega bracket
- 3 digit 7-segment LED display
- Lifting height: 2 m
- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels

Package contents

Logistic

EAN / GTIN: 4026397699395

Weight: 9,40 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- 1 x device, 1 x user manual

Technical specifications:

| | |
|-----------------------|------------------------|
| Weight: | 13,28 kg |
| Noise classification: | Class 2 (slight noise) |

EUROLITE LED Space Tube 100 for HST Hoist

| | |
|----------------------|---|
| Power supply: | 24 V DC |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| LED: | 60 x high-power 3in1 TCL RGB (homogenous color mix) |
| Cooling: | Passive convection cooling |
| Control: | DMX |
| Housing color: | White |
| Dimensions: | Length: 1 m Diameter: Ø 58 cm |
| Weight: | 780 g |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE HST-200 Hoist

| | |
|-----------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 50 W |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | T 1,5 A |
| DMX channels: | 8 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Control: | DMX |
| Preprogrammed in: | LED PC-Control 512 |
| Attachment system: | Omega bracket |
| Display type: | 3 digit 7-segment LED display |
| Lifting height: | 2 m |
| Dimensions: | Width: 23,5 cm Depth: 11 cm Height: 21 cm |
| Weight: | 6,25 kg |
| Noise classification: | Class 2 (slight noise) |
