EUROLITE LED Space Ball 20 + HST-200

Art. No.: 51930479

GTIN: 4026397699401

The article is no longer in our assortment.

Features:

- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended
- <p>EUROLITE LED Space Ball 20
- <p class="featureSatz">Modern LED ambient light with DMX control
- Particularly impressive when used in larger quantities
- 6 powerful LEDs 7 W high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; Dimmer electronic; effect speed adjustable
- The device is cooled by passive convection cooling
- Control via system controller
- For application areas such as: Wedding/gala/events; Clubs/dancing school; restaurants, bars and hotels

Package contents

- 1 x device
- <p>EUROLITE HST-200 Hoist
- <p class="featureSatz">Hoist for LED Space Balls 20, 35 and LED Space Tube 100
- Control via DMX
- Preprogrammed in LED PC-Control 512
- With Omega bracket
- 3 digit 7-segment LED display
- Lifting height: 2 m
- For application areas such as: Clubs/dancing school; Wedding/gala/events; restaurants, bars and hotels
- Application possibility: Suspended

Package contents

- 1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397699401

Weight: 8,50 kg

Length: 0.61 m

Width: 0.31 m

Heigth: 0.42 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Weight:	6,87 kg
Noise classification:	Class 2 (slight noise)

EUROLITE LED Space Ball 20

Power supply:	24 V
Power consumption:	7,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Via 4-pin screw plug connector (M) mounting version
LED type:	6 x 7 W high-power 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	System controller
Housing color:	White
Dimensions:	Diameter: Ø 20 cm
Weight:	620 g

EUROLITE HST-200 Hoist

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	T 1,5 A
DMX channels:	8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX
Preprogrammed in:	LED PC-Control 512
Attachment system:	Omega bracket
Display type:	3 digit 7-segment LED display
Lifting height:	2 m
Dimensions:	Width: 23,5 cm Depth: 11 cm Height: 21 cm
Weight:	6,25 kg
Noise classification:	Class 2 (slight noise)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.