

EUROLITE LED Strobe COB PRO 8x20W DMX

LED strobe with 8 x 20 W COB LED and adjustable flash frequency

Art. No.: 52200870

GTIN: 4026397544565



List price: 236.81 €

incl. 19% VAT.

Description:

This LED strobe is equipped with 8 x 20-watt COB LEDs and combines strobe, chase and blinder effects. It lets you create both dynamic stage shows and the more low-key effects in between with a single fixture.

You can choose from three different operation modes: master-slave, stand-alone and DMX mode (5 DMX channels). The integrated microphone makes for great light effects to the rhythm of the music.

The fixture has 3-pin DMX connectors as well as an IEC input to connect it to the mains.

Features:

- Elaborate reflector system
- 8 powerful LEDs 20 W COB (chip-on-board) cold white (CW)
- Dimmer electronic; effect speed adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- For application areas such as: Clubs/dancing school; mobile djs / entertainer; Stage
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x device, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397544565

Weight: 2,65 kg

Length: 0.39 m

Width: 0.22 m

Height: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, F 3 A Fuse replaceable
Lamp type:	LED lamp
LED:	8 x 20 W COB (chip-on-board) cold white (CW)
Color temperature:	6500K
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Luminous flux:	4800 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 34,5 cm Depth: 11 cm Height: 18 cm
Weight:	2,35 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,4 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 1,5 mm