


EUROLITE LED Super Strobe ABL

LED lighting effect with threefold effects

Art. No.: 52200920

GTIN: 4026397651812



List price: 296.31 €

incl. 19% VAT.

Description:

The Super Strobe ABL combines three functions in one fixture: It is equipped with 216 cold white SMD LEDs for both dynamic strobe effects and slower blinder effects. Furthermore, the reflecting surface of the stroboscope is illuminated with an extra 144 RGB LEDs creating colorful, atmospheric light effects.

Depending on the selected DMX mode, the color LEDs can be split in up to 48 individual control segments which can be used to create amazing color effects within the fixture.

The Super Strobe ABL has a very wide beam angle which makes both dynamic and calm light effects a great visual experience, even from a lateral view.

The fixture has 3-pin DMX connectors as well as a P-Con input and output to connect it to the mains. For a structured and versatile use, you can choose from 4 different DMX modes with 7, 13, 22 and 148 DMX channels respectively.

Features:

- Flat metal housing with integrated wall holders
- 216 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)-
 LEDs controlled separately
- Strobe effect; Wash effect; Blinder effect
- 17 integrated show programs
- Control via Master/slave function; DMX; stand-alone; Sound to light
- Flicker-free
- With Mounting bracket
- 4 digit 7-segment LED display
- Dimmer electronic; color blend stepless

Logistic

EAN / GTIN: 4026397651812

Weight: 4,65 kg

Length: 0.46 m

Width: 0.15 m

Height: 0.30 m

- Mains input and output for power linking up to 8 units
 - Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
 - For application areas such as: Clubs/dancing school; Stage; restaurants, bars and hotels; mobile djs / entertainer
 - Very quiet working noise
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x light effect, 1 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, F 2 A Fuse replaceable
LED:	216 x 0,5 W SMD 5730 cold white (CW) 144 x SMD 5050 3in1 TCL RGB (homogenous color mix)
DMX channels:	7; 13; 22; 148
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Master/slave function; DMX; stand-alone; Sound to light
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 45,5 cm Depth: 8,5 cm Height: 25,5 cm
Weight:	4,26 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Power cord	
Cable construction:	3 x 1,0 mm ² H05RN-F
Cable length:	Approx. 1,5 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting