

## EUROLITE LED Super Strobe

Strobe with 480 bright SMD 5050 LEDs and DMX

Art. No.: 52200921

GTIN: 4026397656138



List price: 177.31 €

incl. 19% VAT.

### Description:

With its 480 cold white SMD LEDs and the flash frequency adjustable from 1 to 20 Hz, the LED Super Strobe combines stroboscope, blinder and wash effects. It lets you create both dynamic stage shows and the more low-key effects in between with a single fixture. The very wide beam angle of 120° guarantees a great visual experience even from a lateral view. You can choose from three different operation modes: master-slave, stand-alone and DMX mode (1, 2 or 3 DMX channels). The metal housing ensures stability and is equipped with a mounting bracket, 3-pin DMX connectors and a P-Con input and output to connect the fixture to the mains.

### Logistic

EAN / GTIN: 4026397656138

Weight: 4,15 kg

Length: 0.45 m

Width: 0.15 m

Height: 0.30 m

### Features:

- 480 powerful LEDs SMD 5050 cold white (CW)
- Dimmer electronic; effect speed adjustable
- Strobe effect
- Control via DMX
- Preprogrammed in LED PC-Control 512; Light Captain
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
- Very quiet working noise
- Application possibility: Suspended

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

## Technical specifications:

|                          |  |
|--------------------------|--|
| Power supply:            | 100-240 V AC, 50/60 Hz   |
| Power consumption:       | 75 W   |
| Lamp type:               | LED lamp   |
| LED type:                | 480 x SMD 5050 cold white (CW)   |
| Flash rate:              | 1 - 20 Hz  |
| DMX channels:            | 1; 2; 3  |
| DMX input:               | 1 x 3-pin XLR (M) mounting version                                     |
| DMX output:              | 1 x 3-pin XLR (F) mounting version                                     |
| Control:                 | DMX  |
| Preprogrammed in:        | LED PC-Control 512; Light Captain                                      |
| Projection:              | Flicker-free   |
| Beam angle (1/2 peak):   | 120°   |
| Color temperature:       | 6500K  |
| Attachment system:       | Mounting bracket   |
| Display type:            | 4 digit 7-segment LED display  |
| Dimensions:              | Width: 46 cm<br>Depth: 8 cm<br>Height: 25,5 cm                         |
| Weight:                  | 3,75 kg  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Power cord               |  |
| Cable construction:      | 3 x 1 mm <sup>2</sup> H05VV-F  |
| Cable length:            | Approx. 1,5 m  |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm  |
| Material:                | Metal, 2 mm  |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination                           |
| Intended use:            | Show effect lighting   |