

## EUROLITE LED IP PIX Strobe FROST

Art. No.: 52200937

Linkable outdoor spotlight (IP65) with stepless electronic frost for stroboscope, ambient and animation effects

GTIN: 4026397752588



**List price: 320.11 €**

incl. 19% VAT.

### Features:

- 240 LEDs 0.5 W SMD 5050 3in1 TCL RGB<BR>8 segments controlled separately
- 40 LEDs 1 W SMD 3030 2in1 BCL CW/WW<BR>4 segments controlled separately
- Integrated mounting system for toolfree and seamless cluster setups
- Wash effect; strobe effect; ambient effect
- Frost filter electronic stepless; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; running light adjustable; color animations with two adjustable colors
- 20 integrated show programs
- Variable color temperature 3200 K - 6600 K
- Direct color temperature selection for 35 preset values
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- DMX fail mode (blackout; hold; auto; manual)
- With a beam angle of 120°
- Good color rendering index (CRI)
- Monochrome OLED display
- With mounting bracket; with omega bracket
- Built with SEETRONIC connector
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; theater; rental; architecture
- The device is cooled by passive convection cooling
- Silent operation
- Application possibility: Suspended; on stand
- Fixtures available for Light Captain; GDTF (GrandMA3)
- IP65
- With pressure compensation membrane
- Mains input and output for power linking up to 8 units

### Logistic

EAN / GTIN: 4026397752588

Weight: 4,25 kg

Length: 0.42 m

Width: 0.24 m

Height: 0.15 m

## Technical specifications:

|                              |                                                                           |
|------------------------------|---------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                    |
| Power consumption:           | 180 W                                                                     |
| IP classification:           | IP65                                                                      |
| Protection class:            | Protection class I                                                        |
| Power connection:            | Mains input power supply cord with safety plug                            |
| Power output:                | 1 x IP T-Con (F) mounting version                                         |
| Lamp type:                   | LED lamp                                                                  |
| LED type:                    | 240 x 0.5 W SMD 5050 3in1 TCL RGB<br>40 x 1 W SMD 3030 2in1 BCL CW/WW     |
| Flash rate:                  | 1 - 25 Hz                                                                 |
| DMX channels:                | 7; 11; 19; 25; 26; 32; 33; 35                                             |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version IP                                     |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version IP                                     |
| Cooling:                     | Passive convection cooling                                                |
| Control:                     | Stand-alone; sound to light via microphone;<br>master/slave function; DMX |
| Fixtures available for:      | Light Captain; GDTF (GrandMA3)                                            |
| PWM frequency:               | 4000 Hz                                                                   |
| DMX fail mode:               | Blackout; hold; auto; manual                                              |
| Beam angle:                  | 120°                                                                      |
| Beam angle (1/2 peak):       | 120° multicolor                                                           |
| Color temperature:           | 3200K - 6600K adjustable                                                  |
| Color rendering index (CRI): | 80 Ra                                                                     |
| Lamp life:                   | 50000 h                                                                   |
| Distance to wall:            | 500 mm                                                                    |
| Housing color:               | Black matte                                                               |
| Attachment system:           | Ø 12mm<br>Mounting bracket<br>Ø 12mm<br>Omega bracket                     |
| Display type:                | 1 x monochrome OLED display                                               |
| Use of brands:               | Built with SEETRONIC connector                                            |
| Dimensions:                  | Length: 38 cm<br>Width: 10.8 cm<br>Height: 17.65 cm                       |
| Weight:                      | 3.70 kg                                                                   |
| Noise classification:        | Class 0 (no noise at all)                                                 |
| Diameter mounting holes:     | 1 x Ø12mm                                                                 |
| Material:                    | Metal, painted                                                            |
| Cable construction:          | 3 x 1.5 mm² H07RN-F                                                       |
| Cable length:                | Approx. 1.2 m                                                             |
| Material:                    | Metal, painted                                                            |
| Material:                    | Metal, painted                                                            |

|                  |                                              |
|------------------|----------------------------------------------|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

### Scope of delivery:

---

1 x spotlight  
1 x user manual  
1 x power cord  
1 x omega bracket