

EUROLITE LED IP PIX Strobe FROST 5pin

Art. No.: 52200938

Linkable outdoor spotlight (IP65) with stepless electronic frost for stroboscope, ambient and animation effects

GTIN: 4026397752564



Features:

- 240 LEDs 0.5 W SMD 5050 3in1 TCL RGB
8 segments controlled separately
- 40 LEDs 1 W SMD 3030 2in1 BCL CW/WW
4 segments controlled separately
- Integrated mounting system for toolfree and seamless cluster setups
- Wash effect; strobe effect; ambient effect
- Frost filter electronic stepless; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; running light adjustable; color animations with two adjustable colors
- 20 integrated show programs
- Variable color temperature 3200 K - 6600 K
- Direct color temperature selection for 35 preset values
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- DMX fail mode (blackout; hold; auto; manual)
- With a beam angle of 120°
- Good color rendering index (CRI)
- Monochrome OLED display
- With mounting bracket; with omega bracket
- Built with SEETRONIC connector
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; theater; rental; architecture
- The device is cooled by passive convection cooling
- Silent operation
- Application possibility: Suspended; on stand
- Mains input and output for power linking up to 8 units
- Fixtures available for Light Captain; GDTF (GrandMA3)
- With pressure compensation membrane

Logistic

EAN / GTIN: 4026397752564

Weight: 4,25 kg

Length: 0.42 m

Width: 0.24 m

Height: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version Bypass
Lamp type:	LED lamp
LED type:	240 x 0.5 W SMD 5050 3in1 TCL RGB 40 x 1 W SMD 3030 2in1 BCL CW/WW
Flash rate:	1 - 25 Hz
DMX channels:	7; 11; 19; 25; 26; 32; 33; 35
DMX input:	1 x 5-pin XLR (M) mounting version IP
DMX output:	1 x 5-pin XLR (F) mounting version IP Bypass
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light Captain; GDTF (GrandMA3)
PWM frequency:	4000 Hz
DMX fail mode:	Blackout; hold; auto; manual
Beam angle:	120°
Beam angle (1/2 peak):	120° multicolor
Color temperature:	3200K - 6600K adjustable
Color rendering index (CRI):	80 Ra
Lamp life:	50000 h
Distance to wall:	500 mm
Housing color:	Black matte
Attachment system:	Ø 12mm Mounting bracket Ø 12mm Omega bracket
Display type:	1 x monochrome OLED display
Connections:	Input: DMX via 1 x 3-pin XLR (M) mounting version Output: DMX bypass via 1 x 3-pin XLR (F) mounting version
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 38 cm Width: 10.8 cm Height: 17.65 cm
Weight:	3.73 kg
Noise classification:	Class 0 (no noise at all)
Material:	Metal, painted
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, painted

Cable construction:	3 x 1.5 mm² H07RN-F
Cable length:	Approx. 1.2 m
Material:	Metal, painted
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x omega bracket