eurolite®

EUROLITE LED Neon Stick 134cm RGB

LED color tube with floor stand and IR remote control

Art. No.: 52500222

GTIN: 4026397694796



List price: 65.33 €

incl. 19% VAT.

Features:

- Extraordinary lighting for an enchanting atmosphere
- The milky PVC housing provides for a lovely appearance as well as for atmospheric illumination
- 72 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Color change adjustable; color fade adjustable; program speed adjustable; Dimmer electronic
- Direct color selection for 16 preset colors
- Control via IR remote control
- With a beam angle of 180°
- For application areas such as: Wedding/gala/events; Party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; Wall mounting

Package contents

- 1 x light effect, 1 x external mains adapter, 1 x remote control, 1 x stand, 4 x foot, 2 x fixation clip, 6 x screw, 2 x mounting material, 1 x user manual

Logistic

EAN / GTIN: 4026397694796
Weight: 0,60 kg
Length: 1.46 m
Width: 0.07 m
Heigth: 0.07 m
Bulky product

Technical specifications:

Power supply:	12 V DC
Power consumption:	Max. 12 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via Coaxial power connector (M) power supply cord with AC adapter (provided)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable length:	Approx. 0,25 m
LED type:	72 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	IR remote control
Beam angle:	180°
Beam angle (1/2 peak):	180°
Luminous flux:	219 lm
Housing color:	Semi-transparent
Material:	Plastic
Dimensions:	Length: 1,34 m Diameter: Ø 3,1 cm
Weight:	440 g
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	963514
External mains adapter	
Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
IP classification:	IP20
Protection class:	Protection class II
Cable length:	Approx. 1,7 m
Output:	12 V DC; 1 A; 12 W
Color:	Black
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Stand	
Material:	Plastic
Color:	Black
Foot	
Material:	Plastic hard
Color:	Black
Fixation clip	
Material:	Plastic
Color:	Semi-transparent

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.