



Features:

- Rope with thimble and connector
- <p>EUROLITE Steel Rope (SC) 600x3mm black with thimbles
- <h2 class="featureSatz">Installation rope, safety bond, safety</h2>Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble
- <p>EUROLITE Quick Link Typ A-50 black
- <h2 class="featureSatz">Quick link</h2>Complies with DIN 56927:2009-03

Logistic

Technical specifications:

Secured weight (BGV C1):	Max. 5 kg
Strength classification:	1770
Temperature range:	-40° C - +100° C
Weight:	0.05 kg

EUROLITE Steel Rope (SC) 600x3mm black with thimbles

Maximum load WLL (5-fold):	100 kg
Design of the core:	6 x 19 WSC
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm²
Wire surface:	Zinc-plated
Color:	Black
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm Diameter: Ø 0.30 cm
Weight:	0.04 kg
Length weigth:	0.0311 kg/m

EUROLITE Quick Link Typ A-50 black

Maximum load WLL (10-fold):	50 kg
Standard:	DIN 56927:2009-03,
Shape:	A - small opening
Material:	Steel, zinc-plated
Opening:	0-5.5 mm
Dimensions:	Length: 2.90 cm Width: 3.50 cm Depth: 1.90 cm Diameter: Ø 0.30 cm
Weight:	0.01 kg

Scope of delivery:

1 x device