

## EUROLITE Safety Bond A 3x600mm up to 5kg, black (FC)

Approved safety bond

Art. No.: 58010342

GTIN:



**The article is no longer in our assortment.**

### Description:

#### EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

### Logistic

### Features:

Approved safety bond

- Suitable for securing loads above persons
- Round strand rope 6 x 19M with fibre core
- With two thimbles
- 3.5 mm quick link (form A) included
- Test report according to DIN EN 10204 as download
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE Steel Rope (FC) 600x3mm black with thimbles

Installation rope, safety bond, safety

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- 3 x 600 mm
- WLL 100 kg
- Complies with DIN 56927:2009-03 and DIN EN 12385-4:2008-06
- For further information about this product, please refer to the Data Sheet under "Downloads"

### EUROLITE Quick Link Typ A-50 black

Quick link

- Complies with DIN 56927:2009-03
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x device

### Technical specifications:

---

Secured weight (BGV C1):	Max. 5 kg
Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm <sup>2</sup>
Wire surface:	Zinc-plated
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm
Weight:	40 g
Length weigth:	0,0311 kg/m
Temperature range:	-40° C to +100° C
Rope length:	0.60 m
Rope diameter:	3.00 mm
Rope type:	Round strand rope
Nominal tensile strength:	1770 N/mm <sup>2</sup>
Strength classification:	1770

### EUROLITE Steel Rope (FC) 600x3mm black with thimbles

Maximum load WLL (5-fold):	100 kg
Design of the core:	6 x 19 FC
Strength classification:	1960
Standard:	DIN 56927:2009-03, DIN EN 12385-4:2008-06
Nominal tensile strenght of rope:	1770 N/mm <sup>2</sup>
Wire surface:	Zinc-plated
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm
Length weigth:	0,0311 kg/m
Maximum load WLL (5-fold):	100 kg

Maximum load BGV C1 (12-fold):	40 kg
Maximum load (safety):	5 kg
Temperature range:	-40° C to +100° C
Rope length:	0.6 m
Rope diameter:	3.00 mm
Rope type:	Round strand rope
Nominal tensile strength:	1770 N/mm <sup>2</sup>
Strength classification:	1960

#### **EUROLITE Quick Link Typ A-50 black**

Maximum load WLL (10-fold):	50 kg
Standard:	DIN 56927:2009-03,
Shape:	A - small opening
Material:	Steel, zinc-plated
Opening:	0-5,5 mm
Dimensions:	Length: 2,90 cm Width: 3,50 cm Depth: 1,90 cm Diameter: Ø 3 mm
Weight:	10 g