

EUROLITE Safety bond AG-35FA 6x1000mm up to 35kg

Approved safety bond

Art. No.: 58010368

GTIN: 4026397496871











The article is no longer in our assortment.

Description:

EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are manufactured by a renowned German supplier and are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Features:

- Suitable for securing loads above persons
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- 6 mm quick link (form A) included
- Test report according to DIN EN 10204 as download
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Secured weight (BGV C1):

Max. 35 kg

Logistic

EAN / GTIN: 4026397496871

Weight: 0,23 kg Length: 0.17 m Width: 0.18 m Heigth: 0.03 m

Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm²
Wire surface:	Zinc-plated Zinc-plated
Temperature range:	-40° C - +100° C
Dimensions:	Length: 1 m
Length weigth:	0,125 kg/m
Temperature range:	-40° C to +100° C
Rope length:	1.00 m
Rope diameter:	6.00 mm
Rope type:	Round strand rope
Nominal tensile strength:	1770 N/mm²
Strength classification:	1770