

## EUROLITE Steel rope 1400x6mm black

Simple steel rope

Art. No.: 5801044B

GTIN:



**The article is no longer in our assortment.**

### Features:

Simple steel rope

- Suitable for installing light loads
- With two loops
- 6 mm quick link (form A) included
- For further information about this product, please refer to the Data Sheet under "Downloads"

### EUROLITE Steel rope 1400x6mm black without quick link

Simple steel rope

- Suitable for installing light loads
- With two loops
- For further information about this product, please refer to the Data Sheet under "Downloads"

### EUROLITE Quick link Typ A-200 black

Quick link

- Complies with DIN 56927:2009-03
- Nominal size: 6 mm
- Form A (short)
- Galvanized
- Identification number: 200
- Stamp: DIN 56927 A 200
- Test report according to DIN EN 10204 as download
- Complies with DIN 56927:2009-03

### Logistic

- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

|                            |                   |
|----------------------------|-------------------|
| Maximum load WLL (5-fold): | 360 kg            |
| Weight:                    | 310 g             |
| Maximum load WLL (5-fold): | 360 kg            |
| Temperature range:         | -40° C to +100° C |
| Rope length:               | 1.4 m             |
| Rope diameter:             | 6 mm              |
| Weight:                    | 0.3 kg            |

### EUROLITE Steel rope 1400x6mm black without quick link

|                            |                   |
|----------------------------|-------------------|
| Maximum load WLL (5-fold): | 360 kg            |
| Temperature range:         | -40° C - +100° C  |
| Dimensions:                | Length: 1,4 m     |
| Maximum load WLL (5-fold): | 360 kg            |
| Temperature range:         | -40° C to +100° C |
| Rope length:               | 1.4 m             |
| Rope diameter:             | 6 mm              |

### EUROLITE Quick link Typ A-200 black

|                                |                                  |
|--------------------------------|----------------------------------|
| Maximum load WLL (5-fold):     | 400 kg                           |
| Standard:                      | DIN 56927:2009-03,               |
| Dimensions:                    | Width: 5,80 cm<br>Depth: 2,70 cm |
| Maximum load WLL (5-fold):     | 400 kg                           |
| Maximum load BGV C1 (10-fold): | 200 kg                           |
| Identification:                | DIN 56926-A-200                  |
| Temperature range:             | -40° C to +100° C                |
| Diameter:                      | 6 mm                             |
| Form:                          | A - small                        |
| Spanner opening:               | 7.5 mm                           |
| Dimensions:                    | 58 x 27 mm                       |
| Weight:                        | 30 g                             |