



## BLOCK AND BLOCK SIGMA-70 Truss lifter 160kg 5.3m

High-quality truss lift for loads up to 160 kg, made in EU

Art. No.: 59000410

GTIN: 4026397644180



### Features:

- Four-part telescopic ground support
- Safety bolts to lock the different sections at different heights
- Locking bolts in the base area to lock the booms
- Booms with adjustable spindle and steel plate with non-slip rubber base
- Corrosion protection through epoxy coating
- Water level to ensure a vertical position
- Earthing connection
- Transport rolls to move the lift when retracted
- AL-KO 351 PLUS winch: Maximum load 350 kg with automatic holding brake. CE declaration of conformity in compliance with the harmonized standards DIN EN 13157, EN 12100 I and II, EC Machinery Directive 2006/42/CE
- Galvanized steel ropes 6x19+1, manufactured in compliance with the standard 13414-1:2004, tensile strength 1770N/mm<sup>2</sup>
- Material: Carbon steel S-275-J0H, manufactured in compliance with the standards EN10219 and EN10305.5
- Adjustable height
- Made in Europe
- With BGV-C1 test certificate

### Logistic

EAN / GTIN: 4026397644180

Weight: 46,00 kg

Length: 0.36 m

Width: 0.38 m

Height: 1.75 m

Bulky product

### Technical specifications:

Maximum carrying capacity:	160 kg
Minimum load:	25 kg
Nominal tensile strength of rope:	1770 N/mm <sup>2</sup>

Height:	Maximum: 530 cm above 4 sections Minimum: 170 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Truss lifter
Material:	Steel (powder-coated)
Transport dimensions:	175 cm x 36 cm x 38 cm
Base area:	Ø 207 cm
Weight:	43.50 kg

**Scope of delivery:**

---