alutruss

ALUTRUSS BILOCK E-GL22 1500 2-way Cross Beam

2-point truss system

Art. No.: 60302082 GTIN: 4026397572650

L'



List price: 148.75 €

incl. 19% VAT.

Description:

BILOCK E-GL22 2-point truss system BILOCK E-GL22 is a 2-point truss system made of aluminum. The individual elements are connected via two cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The two main chords are made of 50 mm aluminum tube with 2 mm wall thickness and offer a good relation between strength and weight. The braces have a diameter of 20 mm with 2 mm wall thickness and leave enough space for installing couplers, hooks and clamps.

With 290 mm outer dimensions, BILOCK E-GL22 is a stable truss system for higher loads and extended durability. This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres.

Its polished surface makes this universal system a real eyecatcher. Due to its wide range of standard system lengths, corners, circles and accessory, this system is highly versatile and offers unlimited design possibilities.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 -Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

Logistic

EAN / GTIN: 4026397572650 Weight: 4,45 kg Length: 1.50 m Width: 0.30 m Heigth: 0.06 m Bulky product

Features:

- Low weight
- Easy to assemble
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"
- Package contents
- 1 x connection set

Technical specifications:

Easy to assemble
50 mm x 2 mm
TIG-welding
AIMg 5
AISi1MgMn
Alu colored
20 x 2mm
Length: 150 cm
Width: 29 cm
Depth: 5 cm
4 kg