

# **EUROLITE DXT-SP 1in/4out PRO DMX RDM Splitter**

RDM-capable DMX splitter, 1in/4out with signal boost

Art. No.: 70064867 GTIN: 4026397572469



SW PAGE

List price: 296.31 €

incl. 19% VAT.

#### Features:

- DMX splitter for splitting one DMX input signal to 4 DMX outputs
- Input and feed-through output are duplicated on the front and rear panel and connected in parallel
- Switchable filter mode allows all RDM data to be filtered out in order to prevent problems when using fixtures intolerant of RDM
- Bypass function to process signals from older devices similar to DMX signals
- Output frequency adjustable: 22/44 Hz
- Switchable termination resistor
- Outputs galvanically isolated
- Each DMX output can be connected to 32 DMX devices
- Each DMX output with active signal processing
- Control via RDM
- RDM For bidirectional communication over the DMX line<BR>RDM switchable to prevent problems when using fixtures without RDM
- DMX fail mode (hold; blackout; zero values)
- Built with NEUTRIK connector
- Made in Germany

#### Package contents

- 1 x device, 1 x external mains adapter, 4 x foot, 1 x user manual

## **Technical specifications:**

Power supply: 100-240 V AC, 50/60 Hz 12V DC 1000 mA

### Logistic

EAN / GTIN: 4026397572469

Weight: 1,40 kg Length: 0.33 m Width: 0.24 m Heigth: 0.06 m

| Power consumption: | 3,6 W                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------------|
| Power connection:  | Mains input via 4-pin screw plug connector (M) mounting version power supply cord with AC adapter (provided) |
| DMX input:         | 2 x 3-pin XLR (M) mounting version                                                                           |
| DMX output:        | 4 x 3-pin XLR (F) mounting version separate (galvanic) with active signal processing                         |
|                    | 2 x 3-pin XLR (F) mounting version Bypass                                                                    |
| Control:           | RDM                                                                                                          |
| DMX features:      | RDM For bidirectional communication over the DMX line                                                        |
|                    | RDM switchable to prevent problems when using fixtures without RDM                                           |
| DMX fail mode:     | Hold; blackout; zero values                                                                                  |
| Use of brands:     | Built with NEUTRIK connector                                                                                 |
| Dimensions:        | Width: 27,5 cm                                                                                               |
|                    | Depth: 10 cm                                                                                                 |
|                    | Height: 4,1 cm                                                                                               |
| Weight:            | 1,21 kg                                                                                                      |