

## EUROLITE ESN 7x80 USB LAN LED Moving Message

Art. No.: 80500107

RG moving message display (7x80 pixels) with network connectivity, PC software and IR remote control

GTIN: 4026397681314



**List price: 296.31 €**

incl. 19% VAT.

### Features:

- Fully programmable via supplied IR remote control or with PC software via USB port and RJ45 network port
- Dot matrix with 560 super bright SMD LEDs
- Large database with various display effects, symbols and graphics
- 99 editable memory locations
- 8 editable bitmap memory locations, 7 font sizes, 16 color combinations, 8 display speeds, 24 display effects, 30 integrated symbols
- 8 animated messages (Welcome, Merry X'Mas, Happy New Year etc.)
- Programming of sequences
- Timer function
- 560 powerful LEDs SMD 3535 R/G
- The device is cooled by passive convection cooling
- Control via IR remote control; network cable; via USB; wired remote control
- With mounting bracket
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; wedding/gala/events; clubs/dancing school; restaurants, bars and hotels

#### Package contents

- 1 x device, 1 x external mains adapter, 1 x USB stick, 1 x remote control, 1 x USB cable, 1 x network cable, 2 x angle, 2 x battery

### Logistic

EAN / GTIN: 4026397681314

Weight: 1,59 kg

Length: 0.84 m

Width: 0.08 m

Height: 0.17 m

### Technical specifications:

Power supply: 5V DC

Power consumption: 12 W

|                          |   |
|--------------------------|---|
| IP classification:       | IP20  |
| Protection class:        | Protection class III  |
| Power connection:        | Mains input via coaxial power connector (M)<br>mounting version power supply cord with AC<br>adapter included |
| Battery:                 | 1.5 V AAA Micro LR03 alkaline manganese<br>included   |
| LED type:                | 560 x SMD 3535 R/G  |
| Network connection:      | Protocol: Ethernet TCP/IP via 1x RJ-45 (F)<br>mounting version  |
| Cooling:                 | Passive convection cooling  |
| Control:                 | IR remote control; network cable; via USB; wired<br>remote control  |
| Image:                   | Max. 7x80 px  |
| Presentation:            | 1-line, 13 visible characters<br>16 colors  |
| Text:                    | 7 fonts   |
| Housing color:           | Black   |
| Attachment system:       | 2x mounting bracket   |
| USB port:                | USB 2.0, type micro USB (F) mounting version  |
| Display:                 | 60,5 cm x 5,5 cm  |
| Dimensions:              | Width: 64,7 cm<br>Depth: 9,7 cm<br>Height: 3,5 cm   |
| Weight:                  | 1,25 kg   |
| External mains adapter   |   |
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Pin configuration:       | Inside + / outside -  |
| IP classification:       | IP20  |
| Protection class:        | Protection class II   |
| Cable length:            | Approx. 1,5 m   |
| Output:                  | 5 V DC; 3 A; 15 W   |
| Color:                   | Black   |
| Remote control           |   |
| Battery:                 | 2 x Micro (AAA) included  |
| USB cable                |   |
| Cable length:            | Approx. 1,5 m   |
| Plug A:                  | 1 x USB, type A   |
| Plug B:                  | 1 x micro USB (M)   |
| Color:                   | Black   |
| Network cable            |   |
| Cable length:            | Approx. 1,5 m   |
| Connector type:          | RJ-45 (M)   |
| Color:                   | Black   |
| Angle                    |   |
| Diameter mounting holes: | 1 x Ø8mm; 1 x Ø6mm  |

|           |               |
|-----------|---------------|
| Material: | Metal, 1,4 mm |
| Color:    | Black, matte  |