

## EUROLITE LSD AIO Network control system

All-in-one network control system LED Show T9 for LED Soft Displays

Art. No.: 80503300

GTIN: 4026397390186



**The article is no longer in our assortment.**

### Features:

- Complete network control system including network interface and software LED show T9 on CD-ROM for controlling LED soft displays with a network-compatible computer
- Ideal control system for mobile use with notebooks with 1 Gbps NIC - requires no additional video card
- 1 network interface allows control of 128 x 128 pixels
- Serial connection of network interfaces possible for control of up to 1024 x 896 pixels
- 8 data signal outputs (each controls 128 x 16 pixels) for connection to LED display panels
- Ethernet input and output, LAN cable included
- System requirements: separate 1 Gbps NIC, Windows 2000/XP/Vista, >1.8 GHz CPU, >1 GB disk space
- Power supply via LED soft displays
- Software functions:
  - supports movies, flash, pictures, and live camera input
  - audio-driven flash animations
  - multiple screen output
  - automated effect parameters
  - up to 6 simultaneous
  - mix up to 3 layers using 18 different overlay
  - user-definable transitions and masks
  - scratch video
  - control playback speed and direction
  - file browser with clip information and preview
  - supports TheaterMode for ATI video cards
  - compatible to media software such as MADRIX

### Logistic

EAN / GTIN: 4026397390186

Weight: 2,04 kg

Length: 0.33 m

Width: 0.30 m

Height: 0.07 m

## Technical specifications:

---

Dimensions:	Width: 16 cm Depth: 4,8 cm Height: 13 cm
Weight:	1,84 kg
Power supply:	5 V DC via display
Signal input:	LAN, CAT5E
Signal link:	LAN, CAT5E
Signal output:	8 x 15-pin DIN jack
Serial connection:	max. 56 units
Resolution:	max. 1024 x 896 pixels
Dimensions (L x W x H):	160 x 130 x 48 mm