

EUROLITE LSD Receiving card MK2

Receiver interface of network control system LED Studio

Art. No.: 80503311

GTIN: 4026397480320



The article is no longer in our assortment.

Features:

- Receiving interface for controlling LED soft displays with a computer
- For operation, the optional control system consisting of sending card and software LED studio (80503130) is required
- 1 receiving interface allows control of 128 (W) x 128 (H) pixels
- Serial connection of receiving interfaces possible for control of up to 1280 (W) x 1024 (H) pixels
- Multiple receiving interfaces can be controlled by one sending card
- Maximum distance between sending card and receiving interface: approx. 100 m
- 8 data signal outputs (each controls 128 (W) x 16 (H) pixels) for connection to LED display panels
- RJ-45 input and output
- Power supply via LED soft displays
- Supported files: text, word documents, all images (BMP, JPG, GIF, PCX...), all video (MPG, MPEG, MPV, AVI, VCD, DVD, SWF, RM, RMJ, ASF, MOV, etc.)

Logistic

EAN / GTIN: 4026397480320

Weight: 2,06 kg

Length: 0.35 m

Width: 0.25 m

Height: 0.08 m

Technical specifications:

Dimensions: Width: 16 cm
Depth: 4,8 cm
Height: 13 cm

Weight: 1,87 kg

Power supply: 5 V DC via LED display

Signal input: LAN, CAT5E

Signal link:	LAN, CAT5E
Signal output:	8 x 15-pin DIN jack
Dimensions (L x W x H):	160 x 130 x 48 mm