

OMNITRONIC MPZ-250 PA mixing amplifier

4 zone PA mixing amplifier switchable zones, 250 W RMS

Art. No.: 80709730

GTIN: 4026397176360



The article is no longer in our assortment.

Features:

- Comfortable control of your PA speakers via 4-zone technology
- 4 PA zone outputs, independently switchable on the front panel
- Master PA output (70 V and 100 V)
- Output for low-impedance speakers (4-16 ohms)
- 3 microphone inputs (6.3 mm jack, unbal.) with separate level controls
- Microphone input 3 with adjustable priority circuit
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-fold LED level display
- Master control for the output signal
- Fan-cooled
- Protection circuits with LED indication: over current, short circuit, turn-on delay
- Rack installation, brackets detachable

Logistic

EAN / GTIN: 4026397176360

Weight: 13,70 kg

Length: 0.55 m

Width: 0.48 m

Height: 0.20 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Output power: 250 W RMS

Frequency range: 80 - 16000 Hz

Zone output: 4 switchable zones

Dimensions: Width: 48,3 cm

Depth: 38,5 cm
Height: 8,9 cm

| | |
|--------------------|----------------------------------|
| Output power: | 250 W RMS |
| Output type: | 70 V, 100 V or 4-16 ohms |
| Output current: | |
| 70 V | 3.6 A |
| 100 V | 2.5 A |
| Mic input: | 5 mV, 600 ohms |
| Line input: | 300 mV, 10 kohms |
| Output connectors: | Screw connectors, terminal block |
| Distortion: | 0.5 % (1 kHz) |
| S/N ratio: | |
| Aux: | 85 dB |
| Mic: | 75 dB |
| Dimensions: | 483 x 385 x 92 mm |
| Weight: | 14 kg |
