

## **OMNITRONIC MAVZ-360.6P PA Mixing Amplifier**

#### Art. No.: 80709793

6-zone-PA mixing amplifier with audio player, IR remote control and Bluetooth, adjustable zones, 360 W RMIS: 4026397703641









# List price: 653.31 €

incl. 19% VAT.

#### Features:

- Comfortable control of PA speakers via 6-zone technology
- 6 PA zone outputs with separate 5-step level controls
- Output for low-impedance speakers (4-16 ohms)
- SD card slot and USB port
- Folder navigation, repeat functions and random play
- 3 microphone inputs with separate level controls
- Mic 1 with phantom power and priority circuit
- Mic 2 and 3 switchable mic/line
- 2 line inputs with separate level controls
- 1 line output
- Treble and bass and master controls for the output signal
- 5-digit LED level meter
- Chime, switchable
- (19") 48.3 cm rack installation 2 U
- The device is cooled by cooling fan
- Control via IR remote control; Bluetooth
- LCD display
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms Package contents
- 1 x amplifier, 1 x remote control, 1 x battery, 2 x holder, 4 x screw, 1 x user manual

#### **Technical specifications:**

Power supply:

230 V AC, 50 Hz

### Logistic

EAN / GTIN: 4026397703641 Weight: 8,55 kg Length: 0.53 m Width: 0.44 m Heigth: 0.18 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	720 W
Protection class:	Protection class I
Output power:	360 W RMS
Power connection:	Fixed power supply cord with safety plug
Device fuse:	5 x 20 mm, T 6,3 A fuse replaceable
Frequency range:	50 - 18000 Hz
S/N ratio:	>75 dB microphone
	>85 dB line
THD:	<0,5 % at 1 kHz
Cooling:	Cooling fan
Impedance:	Public address systems 100V; 4-16 ohms; Public address systems 70V
Control:	IR remote control; Bluetooth
Bluetooth device name:	Bluetooth
Audio player:	USB + SD + Bluetooth
Housing color:	Black
Zone output:	6 adjustable zones
Circuitry:	Class AB
Display type:	LCD display
Control elements:	Power switch, Master control, level control per channel, tone control, phantom power switch
Controls:	Power on/off transient; Overvoltage; short-circuit
Status LED:	Power, fault, clip, level meter
Connections:	Input: microphone via 2 x 6.3 mm plug (unbal.) Input: microphone via 1 x 3-pin XLR Input: line via 3 x stereo RCA 0,3 V Output: line via 1 x stereo RCA 0,3 V Output: speaker via screw terminal
Equalizer:	Master: 1 x 2-band tone control mono
Music format:	MP3
Number of files:	Max. 999
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 27,5 cm Height: 9,6 cm
Weight:	7,15 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in