

OMNITRONIC PAP-120 PA Amplifier

PA power amplifier, 120 W RMS

Art. No.: 80709806

GTIN: 4026397582062



List price: 320.11 €

incl. 19% VAT.

Features:

- 1 line input (optionally XLR or 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- Load detection and power control
- Highly efficient Air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Package contents

- 1 x amplifier, 1 x user manual

Logistic

EAN / GTIN: 4026397582062

Weight: 10,50 kg

Length: 0.54 m

Width: 0.47 m

Height: 0.18 m

Technical specifications:

| | |
|-------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Output power: | 120 W RMS |
| Power connection: | Fixed power supply cord with safety plug |
| Frequency range: | 60 - 16000 Hz |
| S/N ratio: | >90 dB |
| THD: | <0,5 % at 1 kHz |
| Cooling: | Temperature-controlled fan , Air flow from front to rear |

| | |
|-------------------|--|
| Impedance: | 4-16 ohms speaker; Public address systems 100V speaker; Public address systems 70V |
| Circuitry: | Class AB |
| Control elements: | Level control, power switch |
| Controls: | Softstart; overheat; overload; short-circuit; DC voltage |
| Status LED: | Power, signal, fault, clip |
| Connections: | Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR (F) mounting version 0,8 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR (M) mounting version Output: speaker via screw terminal |
| Material: | Metal |
| Color: | Black |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm Depth: 38,5 cm Height: 8,9 cm |
| Weight: | 8,85 kg |