

OMNITRONIC GCA-510S Ceiling Speaker 10W/p

Hi-fi ceiling mount speaker with firedome

Art. No.: 80710129

GTIN: 4026397349184



The article is no longer in our assortment.

Features:

- High performance 2-way system with 13 cm woofer (5") and 4 cm silk dome tweeter (1.5") for superior sound
- Convincing SPL, frequency range and playback quality
- Large back can for deeper bass response
- For 8-ohm and 100 V systems
- Front-mounted 4-step power selector
- Seismic safety points, strain relief, loose cable ends
- Firedome for safety in case of fire
- Sturdy steel grille in white
- Easy and super quick installation via 4-point clamp system
- Incl. mounting brackets - no additional accessories needed
- Perfect for amplifying conventional rooms

Logistic

EAN / GTIN: 4026397349184

Weight: 7,05 kg

Length: 0.29 m

Width: 0.29 m

Height: 0.64 m

Technical specifications:

| | |
|------------------|---|
| Frequency range: | 70 - 22000 Hz |
| Speaker: | 1 x woofer 5" |
| Dimensions: | Width: 23,4 cm Depth: 23,4 cm Height: 21 cm |
| Input: | 100 V or 8 ohms |
| Components: | 13 cm woofer (5"), 4 cm tweeter (1.5") |

| | |
|-------------------------|---------------------|
| Rated power (100 V): | 1.25/2.5/5/10 W RMS |
| Rated power (8 ohms): | 10 W RMS |
| Sensitivity: | 88 dB |
| Maximum SPL: | 107 dB |
| Dimensions (L x W x H): | 234 x 234 x 210 mm |
| Weight: | 2.7 kg |