



GE 40361 PAR-30 240V/75W flood 2000h

PAR-30 lamp

Art. No.: 88041100

GTIN: 0043168403610



The article is no longer in our assortment.

Features:

- Halogene lamp, suitable for E-27-socket (230 V~)
- Clear, brilliant halogene light for spot (10°) or Flood (30°)
- Operation at mains voltage without transformer
- Front screen provides for low bleaching and protects against contact with and soiling of burner
- Easy replacement with normal E-27 reflector lamps
- Average lifetime 2000 hours
- Constant light flow and no blackening of the burner during lifetime
- Any burner position possible
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 0043168403610

Weight: 0,18 kg

Length: 0.10 m

Width: 0.10 m

Height: 0.10 m

Technical specifications:

Operating voltage:	240 V, 220 - 240 V
Nominal wattage:	75 W
Base:	E27
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike

Beam angle:	30°
Color of light:	White
Color temperature:	2900K
Color rendering index (CRI):	100 Ra
Lead time:	0 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	10° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	650 lm
Dimensions (LxD):	92x95 mm
Legal specifications	
Energy efficiency class (A++ - E):	D