



L'article n'est plus disponible.

Caractéristiques:

FUTURELIGHT DMH-90 LED Moving Head

High performance LED Moving Head with LUMINUS CBM-360 LED

- 1 extra bright LUMINUS CBM-360 LED for best luminance
- 16, 18 or 19 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory

Logistique

- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Commandé via Commande de la musique via Microphone; DMX; RDM

ROADINGER Flightcase 2x DMH-90/DMH-150

PRO flightcase for 2 x FUTURELIGHT DMH-90/DMH-150 LED moving-head

- Developed for 51841950 FUTURELIGHT DMH-90 LED Moving Head, 51841970 FUTURELIGHT DMH-150 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

| | |
|---------------------------|--|
| Poids: | 56,00 kg |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |

FUTURELIGHT DMH-90 LED Moving Head

| | |
|-------------------------------------|--|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 200 W |
| Mouvement de basculement max. TILT: | 270° Positionnement |
| Mouvement de pivotement max. PAN: | 630° Positionnement |
| Gobos: | Diamètre externe 27mm Diamètre de l'image 22mm |
| Canaux DMX: | 16; 18; 19 |
| Commande: | Commande de la musique via Microphone; DMX; RDM |
| Angle de départ (1/2 pic): | 14° |
| Couleur: | Noir |
| Dimension: | Largeur : 34,3 cm Profondeur : 25 cm Hauteur : 42,8 cm |
| Poids: | 13,70 kg |
| DMX channels: | 16/18/19 |
| DMX connection: | 3-pin XLR |

| | |
|--------------------------------|--|
| Sound-control: | via built-in microphone |
| LED type: | LUMINUS CBM-360 |
| LED number: | 1 |
| Beam angle: | 14° |
| Color-wheel: | 8 dichroic filters plus open |
| Rotating gobo-wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 22 mm |
| Maximum PAN-movement: | 630° |
| Maximum TILT-movement: | 270° |
| Dimensions (L x W x H): | 343 x 250 x 428 mm |
| Spécifications juridiques | |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |

ROADINGER Flightcase 2x DMH-90/DMH-150

| | |
|---------------------------------|--------------------|
| Charge maximale: | 100 kg |
| Strength: | 7 mm |
| Outside dimensions (W x D x H): | 950 x 470 x 695 mm |
| Inside dimensions (W x D x H): | 920 x 430 x 470 mm |
| Weight: | 30 kg |