



Caractéristiques:

EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Commandé via stand-alone; DMX; commande de la musique via microphone
- Avec un Angle de départ de 60°

ROADINGER Flightcase 2x PMC-16

PRO flightcase for 2 x PMC-16

- Compartments for 2 x PMC-16
- Suitable for 41606200 EUROLITE LED PMC-16x20W COB 3200K and 41606400 EUROLITE LED PMC-16x30W COB RGB
- Interior upholstered with foam

Logistique

- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners
- 2 hinges
- 2 high-quality butterfly locks
- 2 case handles
- Matériel de marque
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

| | |
|------------------|--|
| Poids: | 24,60 kg |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |

EUROLITE LED PMC-16x20W COB 3200K

| | |
|-----------------------------------|--|
| Alimentation électrique: | 100-240 V CA, 50/60 Hz |
| Puissance totale de raccordement: | 275 W |
| Type de lampe: | Lampe LED |
| Fréquence du flash: | 1 - 20 Hz |
| Canaux DMX: | 3; 16; 19 |
| Commande: | Stand-alone; DMX; commande de la musique via microphone |
| Fixtures disponibles pour: | LED PC-Control 512; Light Captain |
| Angle de départ (1/2 pic): | 60° |
| Température de couleur: | 3200K |
| Couleur du boîtier: | Noir |
| Dimension: | Largeur : 31,5 cm Profondeur : 34,5 cm Hauteur : 34,5 cm |
| Poids: | 8,20 kg |
| DMX channels: | 3/16/19 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 20 Hz |
| Sound-control: | via built-in microphone |
| LED number: | 16 |
| LED type: | Array 20 W, white |
| Color temperature: | 3200 K |
| Beam angle: | 60° |
| Dimensions (W x D x H): | 345 x 315 x 345 mm |
| Produit spécial: | Non destiné à l'éclairage de la pièce dans les ménages |
| Utilisation: | Éclairage pour effets de spectacle |

ROADINGER Flightcase 2x PMC-16

| | |
|-------------------------------------|--|
| Charge maximale: | 50 kg |
| Utilisation de la marque: | Matériel de marque |
| Matériau: | Bois multiplex bouleau, 7 mm |
| Couleur: | Marron foncé, laminé |
| Dimension: | Largeur : 39 cm Profondeur : 44,5 cm Hauteur : 43 cm |
| Poids: | 8,20 kg |
| Strength: | 7 mm |
| Outside dimensions (W x D x H): | 390 x 445 x 430 mm |
| Inside dimensions (W x D x H): | 415 x 355 x 335 mm |
| Compartment dimensions (W x D x H): | 355 x 200 x 335 mm |

Contenu de la livraison: