

OMNITRONIC LRS-1402ST Live Recording Mixer

Live recording mixer with 14 inputs

Réf. : 10040229

GTIN: 4026397449143



L'article n'est plus disponible.

Caractéristiques:

- 4 mono input channels with gain control, 3-way EQ, low cut and pan control
- 4 stereo input channels with balance control
- Adjustable FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- Master fader
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

Logistique

EAN / GTIN: 4026397449143

Poids: 2,20 kg

Longueur: 0.33 m

Largeur: 0.29 m

Hauteur: 0.09 m

Données techniques:

Puissance totale de raccordement:	10,00 W
Plage de fréquence:	20 - 20000 Hz
Rapport signal/bruit:	>94 dB
Dimension:	Largeur : 22,5 cm Profondeur : 24,5 cm Hauteur : 5 cm
Poids:	1,80 kg
Power supply:	2 x 18.5 V AC, 350 mA

via supplied PSU

Inputs/sensitivity:

Mic, mono 0.5 mV, combined XLR/6.3 mm jack bal.

Insert 140 mV, 6.3 mm jack unbal.

Line In, stereo 38 mV/150 mV, 6.3 mm jack L/R bal.

Tape In 400 mV, RCA L/R

Outputs/level:

Main Out: 800 mV, 6.3 mm jack L/R unbal.

Control Room max. 3 V, 6.3 mm jack L/R unbal.

FX Send max. 10 V, 6.3 mm jack unbal.

Tape Out 60 mV, RCA L/R

Headphones 6.3 mm jack unbal.

Headphones impedance: >8 ohms

Distortion: <0.04 %

Tone control/channel:

Treble: ± 15 dB at 12 kHz

Middle: ± 15 dB at 2.5 kHz

Bass: ± 15 dB at 80 Hz

Dimensions (W x D x H): 225 x 245 x 50 mm
