

OMNITRONIC CFL-1242 Live mixer

Table de mixage live à 12 canaux

Réf. : 10060300

GTIN: 4026397304725



L'article n'est plus disponible.

Description:

Something for everybody. The smallest unit of this CFL live mixer series disposes of 12, the biggest unit disposes of 32 mono inputs. Normally, live mixers have faders from 70 - 80 mm. The CFL series has remarkably long faders that easily reach 100 mm. Although it is very low-priced, the series is highly resistant and by offering four subgroups and four Aux-Sends it is really well equipped. In total: powerful but not pricy.

Logistique

EAN / GTIN: 4026397304725

Poids: 15,45 kg

Longueur: 0.73 m

Largeur: 0.26 m

Hauteur: 0.68 m

Caractéristiques:

- 12 mono inputs with XLR sockets and balanced line inputs
- +48V phantom power per channel
- 2 stereo inputs via balanced jacks
- 2 stereo effect returns
- Insert for every mono channel
- High pass filter and 3-band EQ with semi-parametric mids for all mono inputs
- 4 groups for levelling complete signal groups (e.g. drums)
- Mutes for every channel
- 4 aux send (2 pre, 2 post) per channel for controlling the effects and for monitoring
- Separate master, group, monitor outputs
- 100 mm faders
- Precise 12-digit LED meter in subgroups and stereo master

Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

| | |
|-----------------------------------|--|
| Puissance totale de raccordement: | 40,00 W |
| Dimension: | Largeur : 53 cm Profondeur : 53 cm Hauteur : 16 cm |
| Poids: | 12,80 kg |
| Inputs: | |
| 12 mono | XLR or balanced 6.3 mm jacks |
| 12 inserts | 6.3 mm jacks |
| 2 stereo | 6.3 mm jacks |
| 4 Aux-Return | balanced 6.3 mm jacks |
| Outputs: | |
| 2 Main Out: | XLR or balanced 6.3 mm jacks |
| 1 Monitor | balanced 6.3 mm jack |
| 4 Aux Send: | balanced 6.3 mm jack |
| Rec Out | RCA |
| Frequency range: | 10-60000 Hz, ± 3 dB |
| Dimensions (W x D x H): | 530 x 530 x 160 mm |