

OMNITRONIC MZD-860 Matrix Zone Distributor

Mélangeur à 8 canaux avec 6 sorties et matrice

Réf. : 10304115

GTIN: 4026397374254



L'article n'est plus disponible.

Description:

The OMNITRONIC MZD-860 is a matrix zone distributor of 6 inputs for units with line level (e.g. CD player) and microphones (also phantom-powered) which are freely assignable to each of the 6 outputs. A further stereo line channel connects four units with line level and allows for free assignment. Thus it's possible to supply 6 different PA zones with a mono output by routing different input signals to these zones without having to change the cable configuration. It's also possible to obtain 6 outputs with different mixing as every input has its own level control.

Logistique

EAN / GTIN: 4026397374254

Poids: 5,40 kg

Longueur: 0.55 m

Largeur: 0.26 m

Hauteur: 0.21 m

Caractéristiques:

- 6 microphone/line channels, switchable at the front, with separate gain controls, 2-band equalizer, level control and clip LED
- 1 stereo line channel with 4-way input selector, gain control, 2-band equalizer, level control and clip LED
- Matrix input assignment: each input channel is freely assignable to each of the 6 outputs
- Each microphone input with low-noise preamplifier and optional +48 V phantom power
- 6 mono outputs with level control and 6-digit LED level meter
- Color illuminated buttons
- Inputs: 6 x line (stereo RCA), 6 x microphone (XLR), 4 x aux (stereo RCA)
- Outputs: 6 x master (optionally XLR or RCA)
- Rack installation, 3 U
- (19") 48,3 cm installation en rack 3 HE

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	15,00 W
Branchement électrique:	Alimentation électrique via Appareils froids (M) version encastrable Câble d'alimentation à prise contact de protection (inclus dans la livraison)
Plage de fréquence:	20 - 20000 Hz
Conception du boîtier:	(19") 48,3 cm installation en rack 3 HE
Dimension:	Largeur : 48,3 cm Profondeur : 2 m Hauteur : 13,35 cm
Poids:	4,75 kg
Input impedance:	20 kohms (XLR), 10 kohms (RCA)
Output impedance:	300 ohms (XLR), 150 ohms (RCA)
Input gain:	+12 dB to +60 dB (mic), 0 dB to +12 dB (line)
Channel level:	~ to +6 dB/ 0.5 dB
Output level:	~ to +6 dB/ 0.5 dB
7 x EQ treble:	±12 dB
7 x EQ low:	±12 dB
S/N ratio:	75 dB (mic), 85 dB (line)
THD:	1% (mic), 0.05 % (line)