

## OMNITRONIC LH-070 Active dual DI box XLR

Dual DI box/splitter

Réf. : 10355070

GTIN: 4026397194937



### Caractéristiques:

- Active 2-channel DI box with split mode
- 2 high-impedance XLR signal inputs
- 2 low-impedance XLR outputs
- Switchable to split mode (input 1 routes the signal to both outputs)
- Input sensitivity switchable: +20 dB, 0 dB, -30 dB
- Ground-lift switch eliminates signal interference and ground loop problems
- Phase can be switched
- Hi-cut 10 kHz switchable
- Modern convex housing design with rubber corners for safe positioning
- Stackable
- Cables can be routed under the housing
- Operation with 9 V battery (included)

### Logistique

EAN / GTIN: 4026397194937

Poids: 0,75 kg

Longueur: 0.23 m

Largeur: 0.16 m

Hauteur: 0.10 m

### Données techniques:

|                     |  |
|---------------------|--|
| Batterie:           | 1 x 9,0 V E-Block 6LR61 alcalin au manganèse<br>ci-joint |
| Plage de fréquence: | 10 - 30000 Hz  |
| Dimension:          | Largeur : 15 cm<br>Profondeur : 13 cm<br>Hauteur : 6 cm  |
| Poids:              | 0,55 kg  |

|                       |               |
|-----------------------|---------------|
| Power supply:         | 9 V battery   |
| Current consumption:  | approx. 65 mA |
| Battery life:         | 6-8 hours     |
| Input impedance:      | 470 kohms     |
| Output impedance:     | 600 ohms      |
| Maximum output level: | 6 dBu         |
| Dynamic range:        | >100 dB       |
| Hi cut:               | 10 kHz        |
| Input connectors:     | 2 x XLR, bal. |
| Output connectors:    | 2 x XLR, bal. |
| THD:                  | 0.5 %         |

### **Contenu de la livraison:**

---