

OMNITRONIC GEQ-215 XL Equalizer 2x15-band

2 x Égaliseur graphique 15 bandes

Réf. : 10355530

GTIN: 4026397233216



L'article n'est plus disponible.

Caractéristiques:

- 2-channel version, 2 x 15 frequency controls with 2/3 octave steps
- XL (50 mm) sliding frequency controls with center click
- EQ gain switchable ± 6 dB to ± 15 dB
- Switchable low cut filter
- Separate level control per channel
- Bypass switch allows instant comparison of the original sound with the equalized sound
- 7-fold LED level meter with clip indicator
- Inputs and outputs via 6.3 mm jack sockets (1/4"), XLR sockets and screw terminals
- Groundlift switch
- Rack installation, 2 U

Logistique

EAN / GTIN: 4026397233216

Poids: 4,30 kg

Longueur: 0.55 m

Largeur: 0.25 m

Hauteur: 0.12 m

Données techniques:

| | |
|-----------------------------------|---|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 10,00 W |
| Égaliseur: | 2 x Égaliseur graphique 15 bandes |
| Dimension: | Largeur : 48,3 cm Profondeur : 17,5 cm Hauteur : 8,9 cm |
| Poids: | 3,80 kg |
| Input impedance: | 10/20 kohms (unb./bal.) |

| | |
|-------------------------|---|
| Output impedance: | 300/150 kohms (unb./bal.) |
| In/Out connectors: | XLR, jack, screw connectors |
| S/N ratio: | >95 dB |
| Crosstalk: | >90 dB |
| Distortion: | <0.01 % |
| Frequency range: | 20-20000 Hz, ± 0.5 dB |
| Output level: | -- to +6 dB |
| Control range: | ± 6 dBu or ± 15 dBu |
| Frequencies: | 2 x 25/40/63/100/160/250/400/630 Hz, 1/1.6/2.5/4/6.3/10/16 kHz |
| Low Cut: | 30 Hz, -3 dB |
| Dimensions (W x D x H): | 483 x 175 x 88 mm |